



## Description

The TTRM2002R-D02 SISO Bi-Directional Amplifier is a class AB GaN module with an operating frequency range of 2200 to 2500 MHz. Designed for both military and commercial applications, this amplifier features an input voltage range of +10 to +30 VDC and a saturated RF output power of +40 dBm. With the capability of supporting any signal type and modulation format, all in a low-SWaP package, this unit is ideal for applications where high power-density, efficiency, and linearity are essential.

## TTRM2002R-D02

### TABLE OF CONTENTS

- Product Features and Applications
- Characteristics and Specifications
- Power Supply Specifications
- Mechanical Specifications
- Interface Specifications
- Environmental Specifications
- Protections and Maximum Ratings
- DC/Control Connectors
- Mechanical Drawing

## Features

- Temperature Monitor Output
- Over-Temperature Protection
- Tx/Rx Status Monitor
- Amplifier Status Output
- Manual Tx/Rx Switching
- Under Voltage Protection

## Applications

- Unmanned Systems
- Military or Commercial Radio Systems
- Aircraft Systems
- Military MANET
- UAS, UGV, and USV Video/Data Links
- Point-to-Point and Mesh Networking

## CHARACTERISTICS & SPECIFICATIONS

Specifications subject to change without notice. Typical performance at 28VDC at 25°C in a 50Ω system.

### Tx Specifications (Per Channel)

Parameter	Min.	Typ.	Max	Unit
Operating Frequency	2200	—	2500	MHz
64QAM Power Output 20 MHz BW, -27 dB EVM Limit	33	—	—	dBm
BPSK Power Output 20 MHz BW, -7 dB EVM Limit	40	—	—	dBm
Saturated Power Output CW Sweep at Design Limit	—	40	—	dBm
Small Signal Gain	24	27	—	dB
Small Signal Gain Flatness	—	—	2	dB (peak to peak)
Input Return Loss	—	—	-12	dB
Tx / Rx Switching Time	—	1	2	μS

### Rx Specifications (Per Channel)

Parameter	Min.	Typ.	Max	Unit
Small Signal Gain	13.5	16.5	—	dB
Small Signal Gain Flatness	—	—	2	dB (Peak to Peak)
Noise Figure	—	2	2.5	dB
Input Return Loss	—	—	-9	dB

### Power Supply Specifications

Parameter	Min.	Typ.	Max	Unit	Notes
Supply Voltage Range	10	28	30	VDC	—
RMS Operating Current Draw (Idle)	—	0.2	—	A	28VDC Supply Voltage, Idle in Receive Mode
RMS Operating Current Draw (64QAM Power Output)	—	0.7	—	A	28VDC Supply Voltage, 802.11 WLAN Signal, 50% Duty Cycle
RMS Operating Current Draw (BPSK Power Output)	—	1	—	A	28VDC Supply Voltage, 802.11 WLAN Signal, 50% Duty Cycle

## CHARACTERISTICS & SPECIFICATIONS (CONT.)

Specifications subject to change without notice.

### Mechanical Specifications

Parameter	Value	Unit	Notes
Dimensions (L x W x H)	2.73 x 2.53 x 1.313 (69.3 x 64.3 x 33.4)	in (mm)	—
Cooling	Integrated Heatsink	—	—
Weight	6.8 (193)	oz (g)	—

### Interface Specifications

Parameter	Value	Notes
RF Connectors (Input / Output)	SMA-F / SMA-F	—
Power / Signal Connector	2M801-009-02ZNU7-10PA	Connector appearing on unit (Manufacturer P/N)
Mating Connector	MKJ1A6F7-10SA	Mating connector required for interfacing (Manufacturer P/N)
Test Integration Cable	CBL65	Triad P/N available for purchase separately

### Environmental Specifications

Parameter	Min.	Max	Unit
Operating Temperature (Housing Temp.)	-40	85	°C
Storage Temperature	-55	85	°C
Altitude	0 (0)	30000 (9144)	ft. (m.)
Ingress Protection Rating	IP67		—
Shock / Vibration	Designed to comply with MIL-STD-810 Shock / Vibration Test Methods		—

### Protections & Maximum Ratings

Parameter	Value	Unit	Notes
Maximum RF Input (Per Channel)	33	dBm	CW Power
Over Temp Protection Trip Level	88	°C	Internally Monitored System Temperature
RF Output Open Load Survivability	39	dBm	CW with Open Circuit at Antenna Port

## DC / CONTROL CONNECTORS

## Input / Output Pins

TTRM Connector Part Number			Mating Connector Part Number	
2M801-009-02ZNU7-10PA			MKJ1A6F7-10SA	
Pin	Label	Type	I/O	Notes
1	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
2	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
3	Vin	Power	N/A	Supply Voltage - Range Specified in Data Sheet
8	GND	Power	N/A	Power Supply Return (Ground)
9	GND	Power	N/A	Power Supply Return (Ground)
10	GND	Power	N/A	Power Supply Return (Ground)
4	I/O	Signal	Input	<p>TA: TTL High or No Connection = Enable TTL Low = Disable</p> <p>Manual Switching TTRM: TTL High = Tx Amp Enabled TTL Low = Rx Amp Enabled</p> <p>Automatic Switching TTRM: Pin not required. Do not use.</p>
5	BYPASS	Signal	Input	<p>Bypass Control TTL High or Open = Amplifier Mode GND = Bypass</p>
6	STATUS	Signal	Output	<p>5V TTL Output HIGH = Normal Mode LOW = Error</p>
7	TEMP	Signal	Output	<p>Temperature Monitor Temp in DegC = (Vout - 0.5V) * 100</p>

MECHANICAL DRAWING

